



## Specifications Ledvance LED Downlight Slim Square SQ155 12W 1020lm 120D - 840 Cool White

[View Product](#)

### General Information

|                      |                                      |
|----------------------|--------------------------------------|
| SKU                  | 233379                               |
| EAN                  | 4058075079298                        |
| Manufacturer Code    | 4058075079298                        |
| Brand                | Ledvance                             |
| Manufacturer Name    | DL SLIM SQ155 12W/4000K WT IP20 LEDV |
| Budgetlight warranty | 3 Years                              |
| Average Lifetime (h) | 30000                                |

### Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 12W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                         |                                       |
|-------------------------|---------------------------------------|
| Light colour options    | Single Color                          |
| Driver Included         | Yes                                   |
| Beam Angle (degree)     | 120                                   |
| Luminous Flux (Lumen)   | 1020lm                                |
| Lumen per watt          | 85                                    |
| Power factor            | >0.50                                 |
| Installation Depth (mm) | 50                                    |
| Unified Glare Rating    | < 28 - for hallways and storage rooms |
| Optical Cover           | PC (Polycarbonate)                    |
| Suitable for Outdoor    | No                                    |
| Product Type Category   | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 155x155                       |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Operating Temperature  | -20 to +50                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | DOWNLIGHT SLIM                |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 30  |
| Diameter (mm) | 169 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**